


電磁接觸器、開關 | SD系列 | 直流控制型



機種	電磁接觸器	非可逆		SD-P11(S)	SD-P16(S)	SD-P21(S)
		可逆		SD-2×P11(S)	SD-2×P16(S)	SD-2×P21(S)
	電磁開關	開放型	非可逆	MDO-P11(S)	MDO-P16(S)	MDO-P21(S)
			可逆	MDO-2×P11(S)	MDO-2×P16(S)	MDO-2×P21(S)
		箱型	非可逆	-	-	-
			可逆	-	-	-
箱型附按鈕		非可逆	-	-	-	
額定容量	CNS 2930 CNS 14816 JIS C8201 JEM 1038	單相	100~110V	0.55/0.75/12	0.75/1/16	1.1/1.5/24
			200~220V	1.1/1.5/12	1.5/2/16	2.2/3/24
		三相	200~220V	3/4/12	3.7/5/16	5.5/7.5/24
			380~440V	4/5.5/9	5.5/7.5/12	11/15/21
			500~550V	4/5.5/7	5.5/7.5/10	11/15/17
		AC 3級 額定容量 (kW/HP/A)	AC 1級電阻性負載 (A)		20	30
	連續通電電流(Ith) (A)		20	30	40	
	IEC 60947-4-1 EN 60947-4-1 DIN VDE 0660	三相	240V	3.5/4.5/13	4.5/6/18	5.5/7.5/24
			440V	5.5/7.5/12	7.5/10/16	11/15/21
			550V	5.5/7.5/9	7.5/10/13	11/15/17
			660V	5.5/7.5/7	7.5/10/9	11/15/14
		連續通電電流(Ith) (A)		20	30	32
		UL 508 CSA-C22.2	單相	110~120V	0.5/9.8	1/16
	220~240V			2/12	3/17	3/17
	三相		220~240V	3/9.6	5/15.2	7.5/22
			440~480V	7.5/11	10/14	15/21
			550~600V	10/11	10/11	15/17
	連續通電電流(Ith) (A)		24	30	35	
	補助接點	標準		1a	1a1b	1a1b
		特殊		1b	-	-
附屬裝置	熱動過電流繼電器	二素子		TH-P12(S)	TH-P20(S)	TH-P20(S)
		三素子		TH-P12E(S)	TH-P20E(S)	TH-P20E(S)
		欠相型		TH-P12PP(S)	TH-P20PP(S)	TH-P20PP(S)
	加熱子額定範圍		0.25A 3.3A 0.4A 4.4A 0.6A 6.5A 0.9A 9A 1.2A 11A 1.7A 15A 2.1A	0.25A 3.3A 0.4A 4.4A 0.6A 6.5A 0.9A 9A 1.2A 11A 1.7A 15A 2.1A		

註：S為附加保護蓋



MS-CR11



MS-2×P35T